




# MUR6020PT, MUR6030PT

## Ultra Fast Recovery Diodes



Dimensions TO-247AD



Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	19.81	20.32	0.780	0.800
B	20.80	21.46	0.819	0.845
C	15.75	16.26	0.610	0.640
D	3.55	3.65	0.140	0.144
E	4.32	5.49	0.170	0.216
F	5.4	6.2	0.212	0.244
G	1.65	2.13	0.065	0.084
H	-	4.5	-	0.177
J	1.0	1.4	0.040	0.055
K	10.8	11.0	0.426	0.433
L	4.7	5.3	0.185	0.209
M	0.4	0.8	0.016	0.031
N	1.5	2.49	0.087	0.102

A=Anode, C=Cathode, TAB=Cathode

	$V_{RSM}$	$V_{RRM}$
	V	V
<b>MUR6020PT</b>	200	200
<b>MUR6030PT</b>	300	300

Symbol	Test Conditions	Maximum Ratings	Unit
$I_{FRMS}$	$T_{VJ}=T_{VJM}$	50	A
$I_{FAVM}$	$T_C=115^{\circ}C$ ; rectangular, $d=0.5$	60	
$I_{FRM}$	$t_p < 10\mu s$ ; rep. rating, pulse width limited by $T_{VJM}$	375	
$I_{FSM}$	$T_{VJ}=45^{\circ}C$	$t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	A
	$T_{VJ}=150^{\circ}C$	$t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	
$I^2t$	$T_{VJ}=45^{\circ}C$	$t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	$A^2s$
	$T_{VJ}=150^{\circ}C$	$t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	
$T_{VJ}$		-40...+150	$^{\circ}C$
$T_{VJM}$		150	
$T_{stg}$		-40...+150	
$P_{tot}$	$T_C=25^{\circ}C$	125	W
$M_d$	Mounting torque	0.8...1.2	Nm
Weight		6	g

# MUR6020PT, MUR6030PT

## Ultra Fast Recovery Diodes

Symbol	Test Conditions	Characteristic Values		Unit
		typ.	max.	
<b>I<sub>R</sub></b>	$T_{VJ}=25^{\circ}\text{C}; V_R=V_{RRM}$		200	uA
	$T_{VJ}=25^{\circ}\text{C}; V_R=0.8 \cdot V_{RRM}$		50	uA
	$T_{VJ}=125^{\circ}\text{C}; V_R=0.8 \cdot V_{RRM}$		5	mA
<b>V<sub>F</sub></b>	$I_F=30\text{A}; T_{VJ}=150^{\circ}\text{C}$		0.85	V
	$T_{VJ}=25^{\circ}\text{C}$		1.10	
<b>V<sub>TO</sub></b>	For power-loss calculations only		0.72	V
<b>r<sub>T</sub></b>	$T_{VJ}=T_{VJM}$		4.2	m $\Omega$
<b>R<sub>thJC</sub></b> <b>R<sub>thCH</sub></b>		0.25	1	K/W
<b>t<sub>rr</sub></b>	$I_F=1\text{A}; -di/dt=100\text{A}/\mu\text{s}; V_R=30\text{V}; T_{VJ}=25^{\circ}\text{C}$	35	50	ns
<b>I<sub>RM</sub></b>	$V_R=100\text{V}; I_F=30\text{A}; -di_F/dt=100\text{A}/\mu\text{s}; L \leq 0.05\mu\text{H}; T_{VJ}=100^{\circ}\text{C}$	4	5	A

### FEATURES

- \* International standard package JEDEC TO-247AD
- \* Planar passivated chips
- \* Very short recovery time
- \* Extremely low switching losses
- \* Low I<sub>RM</sub>-values
- \* Soft recovery behaviour

### APPLICATIONS

- \* Rectifiers in switch mode power supplies (SMPS)
- \* Uninterruptible power supplies (UPS)
- \* Ultrasonic cleaners and welders

### ADVANTAGES

- \* High reliability circuit operation
- \* Low voltage peaks for reduced protection circuits
- \* Low noise switching
- \* Low losses
- \* Operating at lower temperature or space saving by reduced cooling

# MUR6020PT, MUR6030PT

## Ultra Fast Recovery Diodes




Fig. 1 Forward current  $I_F$  versus  $V_F$




Fig. 2 Typ. reverse recovery charge  $Q_r$  versus  $-di_F/dt$




Fig. 3 Typ. peak reverse current  $I_{RM}$  versus  $-di_F/dt$




Fig. 4 Dynamic parameters  $Q_r$ ,  $I_{RM}$  versus  $T_{VJ}$




Fig. 5 Typ. recovery time  $t_{rr}$  versus  $-di_F/dt$




Fig. 6 Typ. peak forward voltage  $V_{FR}$  and  $t_{fr}$  versus  $di_F/dt$




Fig. 7 Transient thermal impedance junction to case