




HUR1560

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes



Dimensions TO-220AC



Dim.	Millimeter	
	Min.	Max.
A	12.70	13.97
B	14.73	16.00
C	9.91	10.66
ØD	3.54	4.08
E	5.85	6.85
F	2.54	3.18
G	1.15	1.65
H	2.79	5.84
J	0.64	1.01
L	5.05BSC	
M	4.32	4.82
N	1.14	1.39
Q	0.35	0.56
R	2.29	2.79

A=Anode, C=Cathode, TAB=Cathode

	V _{RSM} V	V _{RRM} V
HUR1560	600	600



Symbol	Test Conditions	Maximum Ratings	Unit
I _{FRMS}	T _C =140°C; rectangular, d=0.5	35	A
I _{FAVM}		15	
I _{FSM}	T _{VJ} =45°C; t _p =10ms (50Hz), sine	110	A
E _{AS}	T _{VJ} =25°C; non-repetitive; I _{AS} =1A; L=180uH	0.1	mJ
I _{AR}	V _A =1.5·V _R typ.; f=10kHz; repetitive	0.1	A
T _{VJ}		-55...+175	°C
T _{VJM}		175	
T _{stg}		-55...+150	
P _{tot}	T _C =25°C	95	W
M _d	mounting torque	0.4...0.6	Nm
Weight	typical	2	g

HUR1560

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes

Symbol	Test Conditions	Characteristic Values		Unit
		typ.	max.	
I_R	$T_{VJ}=25^{\circ}\text{C}; V_R=V_{RRM}$ $T_{VJ}=150^{\circ}\text{C}; V_R=V_{RRM}$		100 0.5	μA mA
V_F	$I_F=15\text{A}; T_{VJ}=150^{\circ}\text{C}$ $T_{VJ}=25^{\circ}\text{C}$	1.15 1.30	1.25 1.55	V
R_{thJC} R_{thCH}		0.4	2.5	K/W
t_{rr}	$I_F=1\text{A}; -di/dt=100\text{A}/\mu\text{s}; V_R=30\text{V}; T_{VJ}=25^{\circ}\text{C}$	35		ns
I_{RM}	$V_R=100\text{V}; I_F=25\text{A}; -di/dt=100\text{A}/\mu\text{s}; T_{VJ}=100^{\circ}\text{C}$		4.9	A

FEATURES

- * International standard package
- * Planar passivated chips
- * Very short recovery time
- * Extremely low switching losses
- * Low I_{RM} -values
- * Soft recovery behaviour
- * RoHS compliant


APPLICATIONS

- * Antiparallel diode for high frequency switching devices
- * Antisaturation diode
- * Snubber diode
- * Free wheeling diode in converters and motor control circuits
- * Rectifiers in switch mode power supplies (SMPS)
- * Inductive heating
- * Uninterruptible power supplies (UPS)
- * Ultrasonic cleaners and welders

ADVANTAGES

- * Avalanche voltage rated for reliable operation
- * Soft reverse recovery for low EMI/RFI
- * Low I_{RM} reduces:
 - Power dissipation within the diode
 - Turn-on loss in the commutating switch

Marking



Ordering Information

Part Number	Package	Shipping	Marking Code
HUR1560	TO-220AC	50pcs / Tube	HUR1560

HUR1560

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes




Fig. 1 Forward current I_F versus V_F




Fig. 2 Reverse recovery charge Q_r versus $-di_F/dt$




Fig. 3 Peak reverse current I_{RM} versus $-di_F/dt$




Fig. 4 Dynamic parameters Q_r , I_{RM} versus T_{VJ}




Fig. 5 Recovery time t_{tr} versus $-di_F/dt$




Fig. 6 Peak forward voltage V_{FR} and t_{tr} versus di_F/dt




Fig. 7 Transient thermal resistance junction to case

Constants for Z_{thjC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.908	0.0052
2	0.35	0.0003
3	0.342	0.017